TURKISH STANDARDS INSTITUTION

CERTIFICATE OF CONSTANCY OF PERFORMANCE 1783-CPR-585

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation-CPR), this certificate applies to the construction product

Scope is given attached.

placed on the market under the name or trade mark of

KONTROL CİHAZLARI SANAYİ VE TİCARET LTD. ŞTİ. Marmara Sanayi Sitesi G Blok No:8-10-15-16-17-12-13-14-23 İkitelli Küçükçekmece-İSTANBUL/TÜRKİYE

and produced in the manufacturing plant

KONTROL CİHAZLARI SANAYİ VE TİCARET LTD. ŞTİ. Marmara Sanayi Sitesi G Blok No:8-10-15-16-17-12-13-14-23 İkitelli Küçükçekmece, İSTANBUL

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 331:1998, EN 331:1998/A1:2010,

under **system 1** for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 12.05.2017 and revised on 15.04.2021 due to content correction and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Ankara, Rev.2, 15.04.2021



Dr. Fırat Hacıoğlu Deputy Director of Directives



TURKISH STANDARDS INSTITUTION

ANNEX OF CERTIFICATE OF CONSTANCY OF PERFORMANCE

Manually operated ball valves and closed bottom taper plug valves for gas installations for buildings

Tip	I Type	520-15	520-20	520-25	520-32	520-40	520-50
Basınç Sınıfı / Pressure Class		MOP 0,5					
Çalışma Basınç Aralığı I Operating Pressure Range		0-0,5x10 ⁵ Pa					
An	ma Boyutu / minal Size	15	20	25	32	40	50
Gaz Ailesi / Gas Family		1-2-3					
Sicaklik Sinifi / Temperature Class		-20°C					
Çalışma Sıcaklık Aralığı I Operating Temperature Range		Between -20°C and 60°C					
Yangına Tepki Sınıfı / Reaction to fire class		Class A1					
Yüksek Sıcaklığa Direnç I Resistance to high temperature		Pass					
Malzeme / Material	Gövde I Body	CW617N					
	Küre I Ball	CW617N					
	Kol / Lever	HRP Sac					
	Somun I Nut	SAE1006					
	Küre Sızdırmazlığı I Ball Seal	PTFE					
Bağlantı / Connections		Threaded connections					
Kumanda / Operation		Manually operated					

3-CPR-585 numbered Constancy of Performance of Certificate. Rev02, 15.04.2021